

Amendments to the Claims:

A listing of the entire set of pending claims (including amendments to the claims, if any) is submitted herewith per 37 CFR 1.121. This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (Original) A simulation system comprising:
 - an event handler that is configured to determine occurrences of events,
 - a node simulator that is configured to simulate each event to determine one or more characteristics associated with the occurrence of the event,
 - a cache that is configured to store the one or more characteristics associated with the occurrence of select events,
 - and
 - a cache controller that is configured to determine whether:
 - to invoke the node simulator to determine the one or more characteristics associated with a subsequent event or
 - to retrieve the one or more characteristics associated with the subsequent event from the cache.
2. (Original) The simulation system of claim 1, wherein
 - the select events correspond to communications from a transmitter to a receiver in a wireless network.
3. (Original) The simulation system of claim 2, wherein:
 - the cache controller is further configured to:
 - determine a transmitter cluster associated with the transmitter,
 - determine a receiver cluster associated with the receiver; and
 - the cache is configured to store the one or more characteristics based on the transmitter cluster and the receiver cluster.

4. (Original) The simulation system of claim 3, wherein
the cache controller determines the transmitter cluster and the receiver cluster based upon factors associated with the event.
5. (Original) The simulation system of claim 3, wherein
the receiver cluster is determined based upon a location of the receiver relative to a location of the transmitter.
6. (Original) The simulation system of claim 3, wherein
the transmitter cluster is determined based upon an output power of the transmitter.
7. (Original) The simulation system of claim 1, wherein:
each event includes factors that influence the determination of the one or more characteristics, and
the cache is configured to store the one or more characteristics based on the factors.
8. (Original) The simulation system of claim 1, wherein:
each event includes factors that influence the determination of the one or more characteristics,
the cache controller is further configured to determine a category associated with the event based on the factors, and
the cache is configured to store the one or more characteristics based on the category.
9. (Original) The simulation system of claim 8, wherein
the cache controller determines the category based on a quantization of one or more of the factors.

10. (Original) The simulation system of claim 8, wherein
the cache controller determines the category based on a defined range of one or more of the factors.
11. (Original) A simulation method comprising:
determining an event to be simulated; and
if a similar event has been simulated previously:
retrieving characteristics associated with the similar event from a cache;
otherwise:
simulating the event to determine characteristics associated with the event, and
storing the characteristics associated with the event in the cache.
12. (Original) The simulation method of claim 11, wherein
determining whether the similar event has been previously simulated includes:
categorizing the event, and
determining whether a similarly categorized event has been previously simulated.
13. (Original) The simulation method of claim 12, wherein
categorizing the event includes quantizing one or more factors underlying the event.
14. (Original) The simulation method of claim 12, wherein
categorizing the event includes clustering components of the event.

15. (Original) The simulation method of claim 11, wherein
the event corresponds to a communication from a transmitter to a receiver;
and
determining whether the similar event has previously been simulated includes:
determining a transmitter cluster corresponding to the transmitter, and
determining a receiver cluster corresponding to the receiver; and
determining whether the characteristics are stored in the cache corresponding
to a communication from the transmitter cluster and the receiver cluster.
16. (Original) The simulation method of claim 15, wherein
determining the transmitter cluster and the receiver cluster is based on one or
more factors underlying the event.
17. (Original) The simulation method of claim 15, wherein
determining the transmitter cluster and the receiver cluster is based on one or
more defined ranges of one or more factors underlying the event.
18. (Original) The simulation method of claim 15, wherein
determining the transmitter cluster is based on an output power of the
transmitter.
19. (Original) The simulation method of claim 15, wherein
determining the receiver cluster is based on a location of the receiver relative
to a location of the transmitter.

20. (Currently amended) A computer-readable medium encoded with a computer program for execution on a computer system that causes the computer system to:

- maintain a schedule of events to be simulated;
- select an event from the schedule of events based on a simulated time;
- determine whether the event is cache-related; and,
- if the event is not cache-related:
 - simulate the event to determine characteristics related to the event;

otherwise,

- if the event is cache-related:
 - determine whether a similar event has previously been simulated; and
 - if the similar event has previously been simulated:
 - retrieve characteristics related to the similar event from a cache;
 - otherwise
 - simulate the event to determine characteristics related to the

event, and

- store the characteristics related to the event in the cache; and
- schedule subsequent events based on the characteristics.

21. (Currently amended) The computer-readable medium-program of claim 20, wherein the computer is further configured to

- determine whether the similar event has been previously simulated by:
 - categorizing the event, and
 - determining whether a similarly categorized event has been previously

simulated.

22. (Currently amended) The computer-readable medium-program of claim 21, wherein the computer is further configured to

- categorize the event by quantizing one or more factors underlying the event.

23. (Currently amended) The computer-readable medium-program of claim 21,
wherein the computer is further configured to
categorize the event by clustering components of the event.

24. (Currently amended) The computer-readable medium-program of claim 20,
wherein:

the event corresponds to a communication from a transmitter to a receiver;
and

the computer is further configured to:

determine whether the similar event has previously been simulated by:

determining a transmitter cluster corresponding to the
transmitter, and

determining a receiver cluster corresponding to the receiver; and

determine whether the characteristics are stored in the cache
corresponding to a communication from the transmitter cluster and the receiver
cluster.

25. (Currently amended) The computer-readable medium-program of claim 24,
wherein the computer is further configured to

determine the transmitter cluster and the receiver cluster based on one or
more factors underlying the event.

26. (Currently amended) The computer-readable medium-program of claim 24,
wherein the computer is further configured to

determine the transmitter cluster based on an output power of the transmitter.

27. (Currently amended) The computer-readable medium-program of claim 24,
wherein the computer is further configured to

determine the receiver cluster based on a location of the receiver relative to a
location of the transmitter.